

Certificate of Analysis



Serviburnu Lube Plant, Serviburnu Turkey

Phone: +90216 544 07 00

Date (mm/dd/yyyy): 12/26/2023

Product: MOBILGEAR 600 XP 68

Batch Number	S3C0921	Type	Drum Fiege
Order Key	71244781	Manufacture Date	12/25/2023
Export# / P.O.#		Destination	
Fill #	S3C0934	Reference #	
Product #	201560401205	T/C #	

Test Description	Method	Test Result
ASTM Color	ASTM D153	L20
Density @ 15 C, kg/l	ASTM D4052	0.8796
Phosphorus, mass%	ASTM D4951	0.043
Emulsion, Time to 37 mL Water, 82 C, min	ASTM D1401	10
Kinematic Viscosity @ 40 C, mm ² /s	ASTM D445	65.8
Foam, Sequence II, Tendency, ml	ASTM D892(Alt)	10
Foam, Sequence II, Stability, ml	ASTM D892(Alt)	0
Infrared Spectrum	MLP13	MATCH
Odor	AMS 1695	PASS
Water, by Crackle Test	AMS 449	NIL
Appearance	AMS 1738	C & B

This material meets the ExxonMobil Sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock. This document is electronically generated and does not require a physical signature to be valid.

Emel Kazimoğlu, Product Quality Assurance Manager
 Quality Assurance Laboratory
 Mobil Oil Turk A.Ş. Serviburnu LOBP
 Serviburnu Cad. No:1
 34825 Beykoz - Istanbul
 Turkey

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

SER5980445_CofA