

Certificate of Analysis

ExxonMobil

Serviburnu Lube Plant, Serviburnu Turkey

Phone: +90216 544 07 00

Date (mm/dd/yyyy): 01/24/2024

Product: MOBIL DELVAC MODERN 15W-40 SUPER DEFENSE V4

Batch Number	S410812	Type	Drum Fiege
Order Key	71249391	Manufacture Date	01/22/2024
Export# / P.O.#		Destination	
Fill #	S410912	Reference #	
Product #	20152040U765	Tractor T	

Test Description	Method	Test Result
ASTM Color	ASTM D1500	L2.0
Density @ 15 C, kg/l	ASTM D4052	0.8665
Kinematic Viscosity @ 100 C, mm ² /s	ASTM D445	14.5
Calcium, mass%	ASTM D4951	0.112
Zinc, mass%	ASTM D4951	0.128
CCS Viscosity -20 C, mPa.s	ASTM D5293	5116
Pour Point, C	ASTM D7346	-36
Foam, Sequence II, Tendency, ml	ASTM D892(Alt)	15
Foam, Sequence II, Stability, ml	ASTM D892(Alt)	0
Infrared Spectrum	MLP13	MATCH
Odor	AMS 1695	PASS
Magnesium, mass%	ASTM D4951	0.104
Appearance	AMS 1738	C & B

This material meets the ExxonMobil Sales specifications established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock. This document is electronically generated and does not require a physical signature to be valid.

Emel Kazimoğlu, Product Quality Assurance Manager
Quality Assurance Laboratory
Mobil Oil Turk A.Ş. Serviburnu LOBP
Serviburnu Cad. No: 19
34825 Etiler/Beşiktaş-İstanbul
Turkey

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

SER5984821_CofA