

Certificate of Analysis

ExxonMobil

Serviburnu Lube Plant, Serviburnu Turkey

Phone: +90216 544 07 00

Date (mm/dd/yyyy): 03/26/2024

Product: MOBILGEAR 600 XP 320

Batch Number	S430960	Type	DRUM
Order Key	71255296	Manufacture Date	03/26/2024
Export# / P.O.#		Destination	
Fill #	S431032	Reference	
Product #	201560401225	T/C	T

Test Description	Method	Test Result
ASTM Color	ASTM D153	L4.5
Phosphorus, mass%	ASTM D4951	0.028
Emulsion, Time to 37 mL Water, 82 C, min	ASTM D1401	20
Kinematic Viscosity @ 40 C, mm ² /s	ASTM D45	311
Foam, Sequence II, Tendency, ml	ASTM D1402(Alt)	0
Foam, Sequence II, Stability, ml	ASTM D892(Alt)	0
Infrared Spectrum	MLP13	MATCH
Odor	AMS 1695	PASS
Water, by Crackle Test	AMS 449	NIL
Appearance	AMS 1738	C & B

This material meets the ExxonMobil Sales Specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. This document is electronically generated and does not require a physical signature to be valid.

Emel Kazimoğlu, Product Quality Assurance Manager
Quality Assurance Laboratory
Mobil Oil Türk A.S. Serviburnu LOBP
Serviburnu Cad. No:19
34825 Beykoz-İstanbul
Turkey

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

SER5995551_CofA