

Certificate of Analysis

ExxonMobil

Serviburnu Lube Plant, Serviburnu Turkey

Phone: +90216 544 07 00

Date (mm/dd/yyyy): 07/29/2023

Product: MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE V1

| | | | |
|------------------------|--------------|-------------------------|------------|
| Batch Number | S371037 | Type | Drum Fiege |
| Order Key | 71227989 | Manufacture Date | 07/27/2023 |
| Export# / P.O.# | | Destination | |
| Fill # | S371128 | Reference # | |
| Product # | 20152040U721 | T/C or T/T | |

| Test Description | Method | Test Result |
|---|----------------|-------------|
| ASTM Color | ASTM D1500 | L4.0 |
| Density @ 15 C, kg/l | ASTM D4052 | 0.8656 |
| Kinematic Viscosity @ 100 C, mm ² /s | ASTM D445 | 14.54 |
| Calcium, mass% | ASTM D4951 | 0.439 |
| Zinc, mass% | ASTM D4951 | 0.119 |
| CCS Viscosity -25 C, mPa.s | ASTM D5292 | 5625 |
| Pour Point, C | ASTM D7346 | -45 |
| Infrared Spectrum | MLP13 | MATCH |
| Odor | AMS 1695 | PASS |
| Appearance | AMS 1738 | C & B |
| Foam, Sequence II, Tendency, no Option A, ml | ASTM D892(Alt) | 20 |
| Foam Seq II, Stability (No Option A), ml | ASTM D892(Alt) | 0 |

This material meets the ExxonMobil Sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspection done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock. This document is electronically generated and does not require a physical signature to be valid.

Emel Kazanoğlu, Product Quality Assurance Manager
 Quality Assurance Laboratory
 Mobil Oil Turkiye A.S. Serviburnu LOBP
 Serviburnu Cad. No:19
 34125 Beykoz - Istanbul
 Turkey

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

SER5956745_CofA