

Certificate of Analysis



Serviburnu Lube Plant, Serviburnu Turkey

Phone: +90216 544 07 00

Date (mm/dd/yyyy): 04/29/2024

Product: MOBILGEAR 600 XP 220

Batch Number	S440996	Type	Drum Fiege
Order Key	71260263	Manufacture Date	04/27/2024
Export# / P.O.#		Destination	
Fill #	S441041	Reference #	
Product #	201560401220	T/C or T/T	

Test Description	Method	Test Result
ASTM Color	ASTM D1500	L4.0
Density @ 15 C, kg/l	ASTM D4052	0.8912
Phosphorus, mass%	ASTM D4951	0.032
Pour Point, C	ASTM D7346	-9
Emulsion, Time to 37 mL Water, 82 C, min	ASTM D1400	15
Kinematic Viscosity @ 40 C, mm ² /s	ASTM D445	214.1
Foam, Sequence II, Tendency, ml	ASTM D892 (Alt)	5
Foam, Sequence II, Stability, ml	ASTM D892 (Alt)	0
Infrared Spectrum	MLP17	MATCH
Odor	AMS 1695	PASS
Water, by Crackle Test	AMS 449	NIL
Appearance	AMS 1738	C & B

This material meets the ExxonMobil Sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock. This document is electronically generated and does not require a physical signature to be valid.

Emel Kazımoğlu, Product Quality Assurance Manager
 Quality Assurance Laboratory
 Mobil Oil Türk A.Ş. Serviburnu LOBP
 Serviburnu Cad. No:19
 34825 Beşiktaş- İstanbul
 Turkey

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

SER6000604_CofA