

## Certificate of Analysis

# ExxonMobil

Serviburnu Lube Plant, Serviburnu Turkey

Phone: +90216 544 07 00

Date (mm/dd/yyyy): 05/06/2024

Product: MOBIL DTE 25 ULTRA

Batch Number	S450495	Type	Drum Fiege
Order Key	71260667	Manufacture Date	05/04/2024
Export# / P.O.#		Destination	
Fill #	S450547	Reference	
Product #	20156010Q040	T/C or T/T	

Test Description	Method	Test Result
ASTM Color	ASTM D1500	L0.5
Density @ 15 C, kg/l	ASTM D4052	0.8578
Calcium, mass%	ASTM D4951	0.0098
Phosphorus, mass%	ASTM D4951	0.0306
Zinc, mass%	ASTM D4951	0.0499
Emulsion, Time to 3 mL Emulsion, 54 C, min	ASTM D1401	5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s	ASTM D445	44.36
Foam, Sequence I, Tendancy, ml	ASTM D892(Alt)	20
Foam, Sequence I, Stability, ml	ASTM D892(Alt)	0
Infrared Spectrum	MLP13	MATCH
Appearance	AMS	C & B

This material meets the Exxon Mobil Sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing, and / or most recent product restock. This document is electronically generated and does not require a physical signature to be valid.

Emel Kazımoğlu, Product Quality Assurance Manager  
Quality Assurance Laboratory  
Mobil Oil Türk A.Ş. Serviburnu LOBP  
Serviburnu Cad. No:19  
34815 Beykoz-İstanbul  
Turkey

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

SER6001597\_CofA